ELEMAX SH13000 & SHT15000

Models				SH13000		SHT15000
Туре				R	LD	R
Generator	Frequency (Hz)			50	60	50
	Туре			2-pole, Field Rotating Type		
	Voltage Regulation System			AVR		
	Phase			Single Three		
	AC Output	Rated Power (KVA)	50Hz	10.0	-	12.0
			60Hz	-	11.8	-
		Maximum	50Hz	11.0	-	13.2
		Power (KVA)	60Hz	-	13.0	-
		Rated Voltag	je (V)	220	120/240	220/380
		Rated Ampere (A)		45.5	49.2 x 2 / 49.2	18.2
	Rated Power Factor (cosφ)				1.0	0.8
Engine	Maker			ROBIN		
	Model			EH72 - 2DS		
	Туре			Air-Cooled, 4-Stroke, V-Twin Cylinder Horizontal P.T.O. Shaft, OHV Gasoline Engine		
	Displacement (CC)			720		
	Net Power (kW)			17.2 (3,600rpm)		
	Ignition System			Flywheel magnet (solid state)		
	Starting System			Electric Starter		
	Engine Oil			1.55		
	Refill Capacity (ℓ)			(inclusive of oil filter's capacity)		
	Lubrication System			Full Pressure with Trochoid pump, Oil cooler and Spin-on, full-flow oil filter		
	Cooling System			Forced Air		
Others	L x W x H (mm)			924 x 665 x 636 (804 with wheels)		
	Dry Weight (kg)	without wheel		175		
	21, 110.9.11 (119)	with wheel		183		
	Fuel Tank Capacity (liters)			38		
	Sound Level 50Hz [dB(A)/7m] 60Hz		50Hz	76	-	76
			-	78	-	
	Continuous Operating 50Hz Hours (hr) 60Hz		5.5	-	5.5	
			-	4.5	-	
	Oil Alert & Auto Shutdown System			Equipped		
	4-wheel kit			Equipped		